



VHF AND UHF TRANSCEIVERS

IC-F110 IC-F210



- **8-Character Alphanumeric Display**
The alphanumeric LCD indicates channel, bank name and decoded text, etc. Various status icons for such functions as an S-meter and output power, etc., enhance the array of information available to the user.
- **128 Memory Channels with 8 Memory Banks**
Up to 128 channels with 8-character channel names can be stored and divided into 8 banks for flexible channel management.
- **6 Prog. Buttons and Independent Volume Knob**
The up/down and P0–P3 buttons allow you to customize the use of the IC-F110/F210 meet your specific needs. The independent volume knob provides quick and easy operation. An advanced radio that is simple to use.
- **Built-in 2-Tone, 5-Tone, CTCSS, DTCS Encoder and Decoder and DTMF Encoder**
Multiple signaling systems are equipped as standard. 8 DTMF auto-dialing memories are available. The optional DTMF decoder UT-108 provides ANI function.
- **4W (typ.) Front-mounted Speaker**
- **Programmable Wide/Narrow Channel Spacing for Each Channel**
- **Optional Voice Scrambler, UT-109/UT-110**



icom Inc.

ADDITIONAL FEATURES

Advanced Multi 2-Tone/5-Tone systems

- Programmable actions when a matched tone is received
 - Bell icon indication ON/OFF/Blink
 - Answer back calls
 - Beep sounds
 - Scan Start/Stop
 - Auto transmission
 - Stun/Kill functions (prevents use of a lost or stolen radio)
 - External out for horn drive (Optional OPC-617 is required)
- 32 Tx and 9 Rx 5-Tone codes available
- 11 Tx and Rx 2-Tone codes available

Other features

- Hook scan function and Hook scan ON/OFF button are assignable
- 10 scanning lists and normal/priority scan
- Power on password
- Reduced chassis length (117.5mm) allows for easier installation
- External I/O terminal socket with optional OPC-617
- SmarTrunkII™ or LTR® Trunking capability with optional UT-105 or UT-111, respectively
- Backlit LCD and keys for night time operations
- Tested to the MIL-STD 810 C, D, E and F specifications

SPECIFICATIONS

GENERAL

- Frequency coverage :
 - IC-F110 136–174MHz
 - IC-F210 400–430MHz
 - 440–490MHz
- Number of channels : Max. 128, 8 banks
- Channel Spacing : 12.5/25kHz, 12.5/20kHz
- PLL channel step : 2.5, 3, 12.5kHz (VHF)
- 5, 6.25kHz (UHF)
- Frequency stability : ±1.5kHz
- Operating temp. range : -25°C to +55°C
- Power supply voltage : 13.2V DC
- Current drain : Tx at 25W 7A
- Rx Max. audio 1200mA
- Stand-by 300mA
- Antenna impedance : 50Ω (SO-239)
- Dimensions : 150(W)×40(H)×117.5(D) mm
- Weight : 800g

TRANSMITTER

- Output power : 25W (at 13.2V DC)
- Max. frequency deviation : ±5.0kHz (wide)
- ±4.0kHz (middle)
- ±2.5kHz (narrow)
- Spurious emissions : 0.25μW (below 1GHz)
- Adjacent channel power : 70dB (wide, middle)
- 60dB (narrow)
- Mic. impedance : 600Ω (8-pin modular)

RECEIVER

- Sensitivity : -4dBμV typ. (emf) (at 20dB SINAD)
- Squelch sensitivity : -4dBμV typ. (emf, threshold)
- Adjacent channel selectivity : 75dB typ. (wide, middle)
- 65dB typ. (narrow)
- Spurious response : 75dB
- Intermodulation : 67dB typ.
- Audio output power : 4.0W typ. at 10% dist./4Ω load
- Ext. SP connector : 2-conductor 3.5(d)mm/4Q

Applicable U.S. Military Specifications

The IC-F110/F210 has been tested to and passed the following MIL-STD requirements and strict environmental standards.

Standard	MIL 810 C		MIL 810 D		MIL 810 E		MIL 810 F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, II
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	—
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	—
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV



Supplied Accessories

- Hand mic. (HM-152)
- DC power cable
- Mounting bracket kit
- Hanger kit
- Key assign stickers

Measurements made in accordance with ETS 300 086. All stated specifications are subject to change without notice or obligation.

OPTIONS

- **HM-152T DTMF MICROPHONE**
- **OPC-617 ACC CABLE**
For external terminal connection.
- **SM-25 DESKTOP MICROPHONE**
Convenient for dispatching, equipped with monitor switch.
- **SP-5/SP-10/SP-22 EXTERNAL SPEAKERS**
Compact and easy-to-install.
Input impedance: 4Ω; Max. input power: 5W
- **UT-105 SmarTrunk II™ Logic Board**
SmarTrunk II is a trademark of SmarTrunk Systems, Inc.
- **UT-108 DTMF DECODER UNIT**
Provides DTMF decode and ANI capabilities.
- **UT-109 VOICE SCRAMBLER UNIT (Version 02)**
- **UT-110 VOICE SCRAMBLER UNIT (Version 02)**
The scrambler systems of the UT-109 and UT-110 are not compatible with each other. Ask your dealer for details.
- **UT-111 LTR® Trunking UNIT**
LTR is a registered trademark of E.F. Johnson Company.



Icom Inc. 1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 URL: <http://www.icom.co.jp/world/index.html> **Count on us!**

Icom America Inc.
2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand
146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.
Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone : +44 (01227) 741741
Fax : +44 (01227) 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.
6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada
Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 952-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) GmbH
Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone : +49 (0211) 346047
Fax : +49 (0211) 333639
E-mail : info@icom-europe.com
URL : <http://www.icomeurope.com>


Icom France S.a
Zac de la Plaine, 1,
Rue Brindejonc des Moulinais BP 5804,
31505 Toulouse Cedex, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Beijing Icom Ltd.
10C07, Long Silver Mansion, No.88, Yong Ding
Road, Haidian District, Beijing, 100039, China
Phone : +86 (010) 5889 5391/5392/5393
Fax : +86 (010) 5889 5395
E-mail : bjicom@bjicom.com
URL : <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.
A.B.N. 88 006 092 575
Unit 1 / 103 Garden Road,
Clayton VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.
Ctra. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska
Sopot, 3 maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolska@icompolska.com.pl
URL : <http://www.icompolska.com.pl>



Icom Inc. (Japan), is an ISO 9001 and ISO 14001 certification acquired company.